

## Fiber Optic Splice Closure for Dome type

### BS912A



Model	BS912A
Size (mm)	Ø268 X 475 mm
Weight (kg)	3,5kg
Inlet Port	9 (1 Oval)
Cable Dia (mm)	8 ~ 28
No. of Tray	12
Tray Capacity	12C (Max, 24C)
Splice Capacity	144C (Max, 288C)
Clamp Method	Heat Shrinkable Tube

### BS712A / BS812A



Model	BS712A	BS812A
Size (mm)	Ø268 X 534 mm	
Weight (kg)	5,5kg	
Inlet Port	7 (1 Oval)	8
Cable Dia (mm)	8 ~ 29	
No. of Tray	12	
Tray Capacity	24C (Max, 48C)	
Splice Capacity	288C (Max, 576C)	
Clamp Method	Heat Shrinkable Tube	

### BS710A / BS810A



Model	BS710A	BS810A
Size mm	Ø268 X 695 mm	
Weight (kg)	9kg	
Inlet Port	7 (1 Oval)	8
Cable Dia (mm)	8 ~ 29	
No. of Tray	10	
Tray Capacity	60C (Max, 120C)	
Splice Capacity	600C (Max, 1200C)	
Clamp Method	Heat Shrinkable Tube	