

Features

- * CE Approved, Class A RFI Shielding
- * SMD, High Stability
- * Low Loss
- * Excellent Return Loss
- * Suitable for MoCA, CATV, Cable-net and other communication systems

Items			
Model	Pass Band	Model	Pass Band
HPF - 50	50 - 1000 MHz	HPF - 240	240 - 1000 MHz
HPF - 54	54 - 1000 MHz	HPF - 380	380 - 1000 MHz
HPF - 65	65 - 1000 MHz	HPF - 470	470 - 1000 MHz
HPF - 70	70 - 1000 MHz	HPF - 500	500 - 1000 MHz
HPF - 85	85 - 1000 MHz	HPF - 550	550 - 1000 MHz
HPF - 174	174 - 1000 MHz	HPF - 950	950 - 2300 MHz

General Specifications	
Item	HPF - 500
Impedance	75 ohm
Pass Band	500 - 1000MHz
Insertion Loss (500-1000MHz)	1.0dB (typ) / 3.0dB (max)
Return Loss (500-1000MHz)	20dB (typ) / 14dB (min)
Stop Band Rejection (5-455MHz)	55dB (typ) / 50dB (min)
Dimensions (incl. M/F connectors)	21(ϕ) x 57(L) mm
Net Weight	48g