

# **Fiber Optic Splice Closure**

**GJS-02-D** 



## **Technical Specifications**

| Outside dimension (Height x Diameter) | mm | 300 ×180                      |
|---------------------------------------|----|-------------------------------|
| Weight (excluding outside box)        | kg | 1,8                           |
| Number of inlet/out ports             |    | 4 (3 round + 1 oval)          |
| Diameter of out ports                 | mm | 3 x 18 mm<br>1 x (44 x 21 mm) |
| Capacity of FOSC                      |    | 48 can be used for 96 (cores) |

## **Main components**

| FOSC cover                     | pcs | 1     |
|--------------------------------|-----|-------|
| Fiber optic splice tray (FOST) | pcs | max 4 |
| Fiber holding tray             | pcs | 1     |
| Base                           | set | 1     |
| Plastic hoop                   | set | 1     |
| Seal fitting                   | pcs | 1     |



#### **Accessories**

| Heat shrinkable protective sleeve      | pcs | 48 |
|--|-----|----|
| Nylon tie                              | pcs | 10 |
| Heat shrinkable fixing sleeve (single) | pcs | 4  |
| Abrasive cloth                         | pcs | 1  |
| Branching clip                         | pcs | 1  |
| Earthing wire                          | pcs | 1  |
| Desiccant                              | bag | 1  |
| Labeling paper                         | pcs | 1  |
| Aluminum foil paper                    | pcs | 3  |
| Insulating tape                        | pcs | 1  |

## **Pictures**



## KST Ltd.

Address: 357 Slivnitza Blvd.,

Sofia, Bulgaria

Tel: +359 2 927-72-56

Fax: +359 2 927-00-14

Web: www.kst-bg.com

E-mail: sales@kst-bg.com