

## Fiber Optic Splice Closure

### GPJ-D M

#### Product information

The GPJ-D M Closure is a 4 hole dome type, mechanical closure that is designed for use in any outside plant environment (direct buried, wall-mounting and aerial) for through or bifurcation cable connection. The case is made from high-quality PP material, and the closure and the foundation plate are joined with a hoop and sealed with silicon gum materials. The closure can be reused.



#### Application

- Aerial
- Wall-mounting
- Direct Buried
- Mechanical sealing

#### Technical Specifications

Outside dimension (Height x Diameter)	mm	288x178
Weight (excluding outside box)	kg	2.1
Number of inlet/out ports	mm	Φ5-Φ22
Cable diameter	mm	3 x 18 mm 1 x (44 x 21 mm)
Capacity		48(cores)

## Accessories

Heat shrinkable protective sleeve	pcs	24
Nylon tie	pcs	8
Labeling paper	pcs	1
Abrasive cloth	pcs	1
Earthing wire	pcs	1
Earthing wire	pcs	1
Desiccant	bag	1
Hanging Hook	pcs	1

## Pictures



## KST Ltd.

Address: 357 Slivnitsa Blvd.,  
Sofia, Bulgaria

Tel: +359 2 927-72-56  
Fax: +359 2 927-00-14

Web: [www.kst-bg.com](http://www.kst-bg.com)  
E-mail: [sales@kst-bg.com](mailto:sales@kst-bg.com)