

RLK8-1200D4-A-4.0mm-IP-Camera-RLC-1224A-Specification			
	Model	RLC-1224A(4.0mm)	
Note:	The camera is only applicable for bundle sale.		
Video & Audio	Image Sensor	1/2.49" CMOS Sensor	
	Video Resolution	Default: 4512X2512 (12 Megapixels) at 20 frames/sec	
	Lens	f=4.0mm; F=1.6, with IR-cut filter	
	Video Format	H.265	
	Field of View	Horizontal: 93°	
		Vertical: 49°	
	Day & Night	Auto-switching with IR-cut filter	
	Infrared Night Vision	30 meters (100ft) (LED: 2pcs/28mil/850nm)	
Color Night Vision	Spotlight: 1pcs/4.3W/6500K/700 Lumens		
Power	Audio	Two-way audio	
	POE	IEEE 802.3af, 48V Active	
Interface	DC Power	DC 12.0V= 1A, <12W	
	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Storage	Micro SD card slot (Max. 256GB)	
Software Features	Audio	Built-in microphone and speaker	
	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)	
		Substream: 4fps - 20fps (default: 10fps)	
	Code Rate	Mainstream: 3072Kbps - 10240Kbps (default: 8192Kbps)	
		Substream: 128Kbps - 1024Kbps (default: 768Kbps)	
	Browsers Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Motion detection/person detection/vehicle detection/pet detection	
	Record Mode	Motion-triggered recording (default); scheduled recording	
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Maximal User Access	20 Users (1 admin account & 19 user accounts); support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)		
Working Environment	Work with	Google Assistant	
	Temperature	Operating temperature: -10° C~+55° C (14° F~131° F)	
	Humidity	Operating humidity: 10% ~ 90%	
Size & Weight	Waterproof	IP66	
	Dimension	Φ117.4*103.8mm	
	Weight	515g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>	